

# NECTRA LED

LED GO!



220-240 V | LED |  | IP40 | IK08 | 

## TECHNICAL PARAMETERS

Ingress protection:	IP40;
Nominal power [W]:	5.00; 7.00; 9.00; 12.00; 15.00; 18.00;
Luminous flux [lm]*:	360 - 1500
Colour temperature [K]:	4000; 3000;
Colour rendering index:	>80;
Energy efficiency class:	A+; A;
Material of the body:	aluminium;
Colour of the body:	white;
Diffuser material:	PC;
Diffuser type:	OPAL;
Mounting version:	recessed;
Working temperature [°C]:	from -15 to +35;
Supply voltage [V]:	220 - 240;
Frequency [Hz]:	50 - 60;
Dimensions [mm]:	∅108/51; ∅116/51; ∅146/67; ∅182/62

\*Tolerance +/- 10%

## CHARACTERISTICS

Downlight type fitting with an integrated energy-saving LED source. Made of lightweight aluminium and plastic. Available in two ringcolours and three power versions. Its distinctive features are low profile, light weight and very easy and fast installation.

## APPLICATION

Design for both solid and modular ceilings.

# NECTRA LED

LED GO!

## AVAILABLE TYPES

[Click >> index, to see details](#)

### NECTRA LED $\varnothing$ 108/51mm

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Energy efficiency class	Index
5	4000	370	OPAL	A+	<a href="#">&gt;&gt; 059537</a>
5	3000	360	OPAL	A+	<a href="#">&gt;&gt; 059520</a>

### NECTRA LED $\varnothing$ 116/51mm

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Energy efficiency class	Index
7	4000	570	OPAL	A+	<a href="#">&gt;&gt; 059568</a>
7	3000	540	OPAL	A+	<a href="#">&gt;&gt; 059551</a>

### NECTRA LED $\varnothing$ 146/67mm

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Energy efficiency class	Index
9	4000	720	OPAL	A+	<a href="#">&gt;&gt; 059599</a>
9	3000	710	OPAL	A+	<a href="#">&gt;&gt; 059582</a>

### NECTRA LED $\varnothing$ 182/62mm

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Energy efficiency class	Index
12	4000	910	OPAL	A+	<a href="#">&gt;&gt; 059629</a>
12	3000	880	OPAL	A+	<a href="#">&gt;&gt; 059605</a>

### NECTRA LED $\varnothing$ 194/62mm

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Energy efficiency class	Index
15	4000	1250	OPAL	A	<a href="#">&gt;&gt; 059667</a>
15	3000	1200	OPAL	A	<a href="#">&gt;&gt; 059643</a>

### NECTRA LED $\varnothing$ 234/67mm

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Energy efficiency class	Index
18	4000	1500	OPAL	A	<a href="#">&gt;&gt; 059704</a>
18	3000	1400	OPAL	A	<a href="#">&gt;&gt; 059681</a>

\*Tolerance +/- 10%

## ACCESSORIES

Name	Index
Round surface casing - white, 12W	059797
Round surface casing - white, 15W	059735
Round surface casing - white, 18W/20W/25W	059759
Round surface casing - white, 15W	059858
Round surface casing - white, 11W	059841



Round surface casing - white,  
12W (059797)



Round surface casing - white,  
15W (059735)



Round surface casing - white,  
18W/20W/25W (059759)



Round surface casing - white,  
15W (059858)



Round surface casing - white,  
11W (059841)

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer.

Revision date: 2019-05-23



Lena Lighting S.A.  
ul. Kórnicka 52  
63-000 Środa Wielkopolska

tel. +48 61 28 60 300  
e-mail: office@lenalighting.pl  
www.lenalighting.pl



The luminaire complies with the EU RoHS Directive 2011/65/UE



This product is a subject to electric and electronic waste equipment regulations (WEEE).



37/2013 ; 37/2014