

POXAR SNF LED

EMERGENCY LIGHTING



IP40

CHARACTERISTIC

Index :	324543
Supply voltage :	220-240V
Frequency :	50/60Hz
Ingress protection IP :	IP40
Rated power :	1W
Emergency lighting :	3H
Dimensions :	299/206/43mm
Material of the body :	PC
Light source :	LED

SPECIFICATION

Surface mounted emergency fitting with a power of 1W, available in maintained and non-maintained versions. The body is made of polycarbonate; PMMA mounting board. NiCd battery life in the event of emergency is 3h. NiCd battery life in the event of emergency is 3h. A bracket for wall mounting available on request.

APPLICATION

The main task of the independent emergency light fitting is to indicate the direction of evacuation routes and emergency exits after a power outage, i.e. in Safe Mode. Suitable for wall or ceiling mounting. Especially recommended in for technical rooms (corridors, stairways, garages, basements) where permanent emergency lighting is required.

POXAR SNF LED

EMERGENCY LIGHTING

TECHNICAL DATA

Index:	324543
Supply voltage:	220-240V
Frequency:	50/60Hz
Ingress protection IP:	IP40
Rated power:	1W
Electrical protection class:	II
Emergency lighting:	3H
Dimensions:	299/206/43mm
Net weight of 1 unit:	0,85kg
Material of the body:	PC
Mounting version:	Surface
Working temperature:	from 0°C to +35°C
(EAN) European Article Number:	5905963324543
Material of the diffuser:	PMMA
Light source:	LED

The company reserves the right to make design changes or upgrades in the presented product.
Product data sheet does not constitute an offer.

Revision date: 2017-05-26



Lena Lighting S.A.
ul. Kornicka 52
63-000 Sroda Wielkopolska

tel. +48 (61) 28 60 300
fax.+48 (61) 28 54 059
e-mail: office@lenalighting.pl
www.lenalighting.pl



The luminaire complies with the EU ROHS Directive 2011/65/UE.



This product is a subject to electric and electronic waste equipment regulations (WEEE).



30/2016