

COMPACT LED EVO Z



OFFICE LIGHTING



CHARACTERISTIC

Supply voltage:	220-240V
Frequency:	50 - 60Hz
Ingress protection IP:	IP20
Rated power:	24W - 52W
Energy efficiency class:	EEL=A++, A+
Electrical protection class:	I, II
Dimensions:	620/620/69mm
Material of the body:	ABS
Colour temperature:	3000K, 4000K
Mounting version:	Suspended
Material of the diffuser:	PC
Type of the diffuser:	Opal / PRM

SPECIFICATION

Compact LED luminaire designed for suspended installation. Equipped with energy-saving LED GO! panels and an evenly highlighted opal or prismatic diffuser, providing low glare. Made of plastic. Assembly or electrical connection does not require removing the diffuser.

APPLICATION

This luminaire is designed for indoor use in offices or general utility rooms. It can be used as the main light source and it is particularly well-suited to be used as a light source for workplaces that require eyesight focus. The luminaire is used both in new applications, as well as it can replace traditional fluorescent luminaires with energy-saving LED solutions.

FEATURES

Standard Deviation Colour Matching (SDCM): ≤ 3

COMPACT LED EVO Z



OFFICE LIGHTING

AVAILABLE OPTIONS

[Click on index to go to detailed catalogue extract](#)

Index	Rated power	Colour temperature	Luminous flux **	Material of the diffuser	Type of the diffuser	Power supply	Electrical protection class	Energy efficiency class
» 628863	32W	3000K	3550lm	PC	Opal		II	A+
» 628849	32W	4000K	3800lm	PC	Opal		II	A+
» 628870	32W	3000K	4250lm	PC	PRM		II	A+
» 628856	32W	4000K	4550lm	PC	PRM		II	A++
» 629761	42W	3000K	4450lm	PC	Opal	DALI	I	A+
» 628900	42W	3000K	4450lm	PC	Opal		II	A+
» 629747	42W	4000K	4800lm	PC	Opal	DALI	I	A+
» 628887	42W	4000K	4800lm	PC	Opal		II	A+
» 629778	42W	3000K	5350lm	PC	PRM	DALI	I	A+
» 628917	42W	3000K	5350lm	PC	PRM		II	A+
» 628894	42W	4000K	5750lm	PC	PRM		II	A++
» 629754	42W	4000K	5750lm	PC	PRM	DALI	I	A++
» 629808	52W	3000K	5050lm	PC	Opal	DALI	I	A+
» 629785	52W	4000K	5450lm	PC	Opal	DALI	I	A+
» 629815	52W	3000K	6100lm	PC	PRM	DALI	I	A+
» 629792	52W	4000K	6550lm	PC	PRM	DALI	I	A+
» 628948	52W	3000K	5050lm	PC	Opal		II	A+
» 628924	52W	4000K	5450lm	PC	Opal		II	A+
» 628955	52W	3000K	6100lm	PC	PRM		II	A+
» 628931	52W	4000K	6550lm	PC	PRM		II	A+
» 628825	24W	3000K	2750lm	PC	Opal		II	A+
» 628832	24W	3000K	3300lm	PC	PRM		II	A+
» 628801	24W	4000K	2950lm	PC	Opal		II	A+
» 628818	24W	4000K	3550lm	PC	PRM		II	A++

** Initial, tolerance +/- 10%

The company reserves the right to make design changes or upgrades in the presented product.
Product data sheet does not constitute an offer.

Revision date: 2017-10-30



Lena Lighting S.A.
ul. Kornicka 52
63-000 Sroda Wielkopolska

tel. +48 (61) 28 60 300
fax. +48 (61) 28 54 059
e-mail: office@lenalighting.pl
www.lenalighting.pl



The luminaire complies with the EU ROHS Directive 2011/65/UE.



This product is a subject to electric and electronic waste equipment regulations (WEEE).



20/2017