

iQ-LED

Kanlux

IQ-LED GU10

LED light source



[V] 220-240 AC	[Hz] 50/60	SMD	ellipse ≤ 6x MacAdam	Ra ≥ 95	≥ 40000	(h) 25000
		A+	CE	EAC		



IQ-LED GU10 5W



	[W]	[lm]	[lm]	Φ _{use}	T _c [K]	[°]	
IQ-LED GU10 5W-WW	29803	5	31	370	335	2700	120 GU10
IQ-LED GU10 5W-NW	29804	5	31	380	340	4000	120 GU10
IQ-LED GU10 5W-CW	29805	5	31	380	340	6500	120 GU10
IQ-LED GU10 7W S3-WW	29806	7	75	580	535	2700	36 GU10
IQ-LED GU10 7W S3-NW	29807	7	75	580	535	4000	36 GU10
IQ-LED GU10 7W S3-CW	29808	7	75	580	535	6500	36 GU10
IQ-LED GU10 7W-WW	29809	7	43	580	520	2700	120 GU10
IQ-LED GU10 7W-NW	29810	7	43	580	520	4000	120 GU10
IQ-LED GU10 7W-CW	29811	7	43	580	520	6500	120 GU10

Kanlux IQ-LED means photo-biological safety, colour temperature friendly to eyes and reliability. Now, all this in a new version with GU10 light bulb base. IQ-LED bulbs ensure full comfort of use and safety, which is confirmed by TÜV Rheinland certificate.

Date of issue: 19.11.2019, 15:01

We reserve the right to make technical changes. The data contained in this material are not legally binding.



IQ-LED GU10

LED light source

- Lampshade material: plastic



IQ-LED GU10 5W



IQ-LED GU10 5W



IQ-LED GU10 5W



IQ-LED GU10 7W S3



IQ-LED GU10 7W



IQ-LED GU10 7W




IQ-LED GU10 7W

iQ LED


Kanlux

IQ-LED GU10

LED light source



IQ-LED GU10 5W



IQ-LED GU10 7W